



CARBO



FUSION™ Activator

FOR INDUSTRIAL USE ONLY

Avoid breathing mist / vapors / spray.
 Wash thoroughly after handling.
 Wear protective gloves / eye protection / face protection.
 Do not eat, drink or smoke when using this product.
 Contaminated work clothing must not be allowed out of the workplace.
 Avoid release to the environment.

FIRST AID

Inhalation: Remove to fresh air. Get medical attention if irritation or symptoms persist.

Skin contact: Remove immediately all contaminated clothing. Flush skin with large amounts of water. Wash contaminated clothing before reuse. If irritation or rash develops or persists, get medical attention.

Eye contact: Flush eyes with water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists, get medical attention.

Ingestion: Rinse mouth. Do not induce vomiting. Get medical attention.

CARBO Ceramics Inc.

**575 N. Dairy Ashford Road, Suite 300
 Houston, Texas 77079**

PHONE: 1-337-367-6151 (Customer Service)

PHONE: 1-800-424-9300 (Emergency-CHEMTREC)

www.carboceramics.com

Refer to Safety Data Sheet

Chemical Name	CAS #	Percent
Modified epoxy resin 1	Trade Secret	25-50
Proprietary epoxy resin 2	Trade Secret	20-45
Proprietary epoxy resin 3	Trade Secret	10-15
Proprietary glycidyl compound	Trade Secret	9-10
Proprietary epoxy resin 4	Trade Secret	4-5

DOT Shipping (Bulk): UN 3082 | Class 9
 Environmentally Hazardous Substance, Liquid, n.o.s.
 (epoxy resin)

Lot No.: _____

Run Date: _____

WARNING!

Causes skin irritation.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 Marine pollutant. Avoid unauthorized release to the environment.
 Collect spillage.

INCIDENT RESPONSE

Extinguishing Media: Water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Foam, alcohol-resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective. Water fog, applied gently, may be used as a blanket for fire extinguishment.

Spills: Contain spill immediately with inert material. Transfer liquids and solid diking material to suitable containers for recovery or disposal. Residual can be removed with solvent.

Waste Disposal: Dispose of contents / container in accordance with local, regional, national, international regulations.